

OVERVIEW

Silicone molding — also known as room temperature vulcanizing (RTV) molding — creates finished products for prototyping, functional testing and short-run production. Considering tool life and cycle times, it is ideal for small quantities (25 - 100 castings) because it offers lead times and costs that are well below that of machining or injection molding.

Silicone molds are made by pouring silicone rubber over a pattern. After curing, the resulting firm but flexible mold can produce parts with extremely complex geometry, intricate detail and tight tolerances. The parts are cast from a silicone mold made with thermoset materials (commonly urethanes) that are available with a vast array of mechanical, thermal and electrical properties.

APPLICATION OUTLINE

The traditional silicone mold-making process uses a machined pattern made of plastic, wood or other materials. This method is often expensive and time consuming, and as pattern complexity rises, lead time and cost also increase.

PolyJet™ 3D printing technology is an innovative alternative to machining patterns for silicone mold making. It builds patterns layer by layer, using data from computer-aided design (CAD) files. With its inkjet-like process, PolyJet delivers extremely high-resolution patterns with smooth surfaces.

As a result, PolyJet patterns are typically mold-ready and have subtle details that can be transferred to the urethane castings. For high-gloss or clear finishes, a little polishing is all that is needed. Additionally, complex and intricate patterns can be made without adding time, cost or challenges to the design process. With PolyJet, silicone molds can be ready to make parts in as little as 24 hours.


For larger quantities of castings or multi-part assemblies, family molds are ideal. These multi-cavity tools can produce several pieces with each casting cycle, but each cavity needs its own pattern. Since machined patterns are made in a series, the mold is delayed. Numerous PolyJet patterns — as long as they don't exceed the capacity of the 3D printer — may be produced in one build, and at a fraction of the time required to make them individually.

CUSTOMER STORY


Over the past 50 years the Adler Trio has become the leading harmonica group in the world. To add richness and vibrancy to its performances, the trio wanted to employ custom harmonica amplifiers.

The amplifiers went through several design iterations, each accompanied by a PolyJet 3D printed prototype. Then, because only 10 finished amplifiers were needed, the designers chose to create them using silicone molding and a PolyJet pattern rather than CNC machining.

The first amplifiers were ready to use in less than a day — and at cost which was 80% less than that of CNC — without sacrificing any details in the housing design. Every rib, boss, attachment point



Silicone mold with PolyJet 3D printed pattern.



Smooth surfaces and crisp details make PolyJet patterns mold-ready.



A silicone mold pattern and mold box are ready for pouring.



Raw urethane castings from a silicone mold.

BENEFITS OF POLYJET

Average lead time savings:

- 70% – 90%

Average cost savings:

- 30% – 85%

Quality:

- Smooth, nearly mold-ready surfaces
- Fine textures and details
- Complex, intricate designs

Efficiency gains:

- Automated pattern-making
- Little or no pattern preparation

POLYJET IS A BEST FIT

Quantity:

- Small volume (5 – 250 castings)

Size:

- 6 mm – 300 mm (0.25 in – 12 in)

Design:

- Complex, intricate and highly detailed

Revisions:

- Design modifications are likely.

Multiples:

- Family or duplicate molds for multi-piece casting

and style line was preserved. Plus, the trio's signature logo was as crisp and sharp on each piece as the music it would later amplify.

Today, the Adler Trio custom harmonica amplifiers can be seen and heard during all of their worldwide concerts.

How does PolyJet compare to traditional methods for Adler?

Method	Production Time	Cost
CNC	14 days	\$1,000
PolyJet	0.5 day	\$100
SAVINGS	13.5 days (96%)	\$900 (90%)



Concert-ready harmonica with silicone-molded amplifier.

CUSTOMER PROFILE

Forward-thinking designers and manufacturers of plastic parts that use silicone molding.

Applications:

- Functional prototyping
- Sales and marketing samples
- Low-volume production

Characteristics:

- Thermoset resins are desirable or acceptable.
- Possess or have access to silicone molding assets.
 - Expertise
 - Tools and equipment

Traditional technology obstacles:

- CNC machining is cost or time prohibitive for:
 - Patterns
 - Injection molds

Application compatibility: (0 – N/A, 1 – Low, 5 – High)

• PolyJet: Design (5) • FDM®: Idea (2), Design (3), Production (3)

Companion and reference materials:

- Technical application guide
 - Document
- Application brief
 - Document
- Video
 - Commercial
 - Success story
 - How It's Used

REFERENCE COMPANIES

Damvig Develop
RAPID PROTOTYPING SOLUTIONS

Nypro
Healthcare

Design Reality
ideas at work

Stratasys | www.stratasys.com | info@stratasys.com

7665 Commerce Way
Eden Prairie, MN 55344
+1 888 480 3548 (US Toll Free)
+1 952 937 3000 (Intl)
+1 952 937 0070 (Fax)

2 Holtzman St.
Science Park, PO Box 2496
Rehovot 76124, Israel
+972 74 745-4000
+972 74 745-5000 (Fax)

ISO 9001:2008 Certified

© 2014 Stratasys Ltd. All rights reserved. Stratasys, Stratasys nautilus logo, FDM and Objet are registered trademarks and PolyJet, Eden260V, Eden350V, Eden500V, FullCure, Objet Studio, Objet24, Objet30, Objet30 Pro, WaveWash, VeroGray, VeroWhite, Digital ABS, Objet 260 Connex, Objet350 Connex, and Objet500 Connex are trademarks of Stratasys Ltd. and / or its subsidiaries or affiliates and may be registered in certain jurisdictions. All other trademarks are the property of their respective owners, and Stratasys assumes no responsibility with regard to the selection, performance, or use of these non-Stratasys products. Product specifications subject to change without notice. Printed in the USA. SSYS-AB-Silicone Molding-1-14

For more information about Stratasys systems, materials and applications, contact Stratasys Application Engineering at 1-855-693-0073 (toll free), +1 952-294-3888 (local/international) or ApplicationSupport@Stratasys.com.

